

## Mini Track Loaders / MT85 Mini Track Loader

# Specifications & Options

Standard
  Optional
  N/A Not Applicable

Units Metric

### Bobcat MT85

|                      |                     |
|----------------------|---------------------|
| Emissions Tier (EPA) | Tier 4              |
| Engine Cooling       | Liquid              |
| Engine Fuel          | Diesel              |
| Displacement         | 900 cm <sup>3</sup> |
| Number of Cylinders  | 3                   |
| Horsepower           | 18.49 kW (25.14 hp) |

## Performance

|                                |          |
|--------------------------------|----------|
| Rated Operating Capacity (SAE) | 386 kg   |
| Tipping Load                   | 1115 kg  |
| Operating Weight               | 1407 kg  |
| Ground Pressure (Rubber)       | 0.34 bar |
| Travel Speed                   | 6.6 km/h |
| Travel Speed - Reverse         | 4.7 km/h |

## Capacities

|           |        |
|-----------|--------|
| Fuel Tank | 26.5 l |
|-----------|--------|

## Hydraulic System

|                                |            |
|--------------------------------|------------|
| Pump Capacity                  | 45.4 l/min |
| System Relief @ Quick Couplers | 199.95 bar |
| Auxiliary Std Flow             | n/a        |

## Dimension

|                                   |         |
|-----------------------------------|---------|
| <b>Length</b>                     | 2697 mm |
| <b>Width</b>                      | 904 mm  |
| <b>Height</b>                     | 1387 mm |
| <b>Height to Bucket Hinge Pin</b> | 2055 mm |
| <b>Length of track on ground</b>  | 1031 mm |
| <b>Reach @ Maximum Height</b>     | 472 mm  |

## Features

|   |                                     |
|---|-------------------------------------|
| <b>Lift-Arm Support</b>                             | <input type="checkbox"/>            |
| <b>Auxiliary Hydraulics</b>                         | <input type="checkbox"/>            |
| <b>Spark Arrestor Muffler</b>                       | <input type="checkbox"/>            |
| <b>Bob-Tach Attachment System</b>                   | <input checked="" type="checkbox"/> |
| <b>Reverse Travel Stop Panel</b>                    | N/A                                 |
| <b>Wide Track</b>                                   | <input checked="" type="checkbox"/> |
| <b>Neutral Start Interlocks</b>                     | <input type="checkbox"/>            |
| <b>Lift Arm Lockout With Manual Bypass</b>          | <input type="checkbox"/>            |
| <b>Tilt Lockout</b>                                 | <input type="checkbox"/>            |
| <b>Built-In Tie Down &amp; Crane/Lift Locations</b> | <input type="checkbox"/>            |
| <b>Ride-on Platform</b>                             | <input type="checkbox"/>            |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.